



Certificate of Conformity

Certificate num.	Registration date	Version	Valid until	
afp - 1014	9-Aug-1996	Number 13	Issue date 26-Apr-2019	30-Apr-2020

Page 1 of 2

Product designation

'Automatic', Model H, 15NS x 8.1K(metric), 66°/79°/93°/141°/182°C, Spr. Pend., Spr. Upr., Horiz. Sidewall, Conv., SR Sprinklers

(Refer to the Schedule/enclosures for further specified details)

Agent/distributor

Kidde Australia
Unit 3, Ground Floor, 10 Ferntree Place, NOTTING HILL, VIC, AUSTRALIA, 3168

Registrant

Kidde Australia
Unit 3, Ground Floor, 10 Ferntree Place, NOTTING HILL, VIC, AUSTRALIA, 3168

Producer

Badger Fire Protection Inc.
Route 29 North, CHARLOTTESVILLE, VA, UNITED STATES, 22906

Conformance criteria and evaluation

The 'Automatic', Model H, 15NS x 8.1K(metric), 66°/79°/93°/141°/182°C, Spr. Pend., Spr. Upr., Horiz. Sidewall, Conv., SR Sprinklers have been evaluated and verified as conforming with the relevant requirements of the following criteria.

1. Underwriters Laboratories - Evaluation and listing, 'UL listing'.

Limitations/conditions of conformance

Limitations/conditions of conformance, where identified on this certificate, are derived from qualifications from evaluation(s) for conformity and/or other related technical documentation. All details with respect to design, assembly and installation instructions and restrictions should be checked against the producer's current technical manual/data sheets and the requirements of the Authority having Jurisdiction.

Specified limitations/conditions, determined from the evaluation for conformity, include the following.

- i. The white polyester coated versions of the 'Automatic', Model H, 15NS x 8.1K(metric), 66°/79°/93°/141°/182°C, Spr. Pend., Spr. Upr., Horiz. Sidewall, Conv., SR Sprinklers are not FMRC-Approved.
- ii. The maximum rated water pressure is 1210 kPa.

This certification is issued within the scope of CSIRO Verification Services – Rules governing ActivFire Scheme and is valid only for the product(s) as submitted for evaluation and verification of conformity, subject to the following conditions.

- Reference to details, limitations and requirements, where documented as a schedule/enclosure with this certificate.
- The Registrant is responsible for their attestation of conformity and ensuring that on-going production complies with the conformance criteria defined in this certificate.
- This certificate will not be valid if any changes or modifications are made to the product which have not been notified and validated by CSIRO Verification Services.
- This certificate is subject to periodical re-validation upon verification that all requirements, as determined by the conformity assessment body, continue to be satisfactorily met by the Registrant.
- This certificate may only be reproduced in its published form, without modification and inclusive of all schedules/enclosures.
- Any changes, errors or omissions, must be submitted in writing and if necessary or requested, substantiated with relevant evidence.
- Any representations, such as advertising or other marketing related activities or articles shall reflect the correct contents of this certificate and conform with all relevant trade practices and consumer protection legislation and regulations.
- Any terms or conditions of use as applicable to content and documentation as published or accessed through web sites administered by the CSIRO Verification Services.

Issued by

David Whittaker
Executive Officer – ActivFire Scheme



Schedule to Certificate of Conformity

Certificate num.	Registration date	Version		Valid until	Page 2 of 2
afp - 1014	9-Aug-1996	Number 13	Issue date 26-Apr-2019	30-Apr-2020	

Producer's description

The 'Automatic', Model H, 15NS x 8.1K(metric), 66°/79°/93°/141°/182°C, Spr. Pend., Spr. Upr., Horiz. Sidewall, Conv., SR Sprinklers are automatic sprinklers of the frangible bulb type. They are "standard response - standard orifice spray sprinklers" and, with the exception of the 'Conventional' type deflector version, produce a hemispherical water distribution pattern below the deflector.

Technical specification

The following details are a representative extract of the technical specification for the 'Automatic', Model H, 15NS x 8.1K(metric), 66°/79°/93°/141°/182°C, Spr. Pend., Spr. Upr., Horiz. Sidewall, Conv., SR Sprinklers and may be subject to change. Complete and current details should be determined from the designated producer's technical manual/data sheets.

Actuating element:	Standard response, 5mm glass bulb
Temperature ratings:	57°, 68°, 79°, 93°, 141°, & 182°C
K Factor (Metric):	8.1(l/min, kPa)
Orifice size (Nom):	15 mm
Deflector types:	Spray Pendent, Spray Upright, Conventional, Horizontal Sidewall
Thread size:	15 (mm)

Supplementary information

Finishes:	Available in natural brass, chrome plated, wax-coated, wax-over-lead coating, lead-coated, and white polyester finishes.
------------------	--