



Certificate of Conformity

Certificate num.	Registration date	Version	Valid until	
afp - 1228	17-Feb-1999	Number 8	Issue date 1-May-2013	30-Apr-2014

Page 1 of 2

Product designation

BB Battery, BP Series, sealed, lead acid batteries

(Refer to the Schedule/enclosures for further specified details)

Agent/distributor

Eaton Industries Pty Ltd
10 Kent Road, MASCOT, NSW, AUSTRALIA, 2020

Registrant

Eaton Industries Pty Ltd
10 Kent Road, MASCOT, NSW, AUSTRALIA, 2020

Producer

B & B Battery (USA) Inc.
6415 Randolph Street, CITY OF COMMERCE, CA, UNITED STATES, 90040

Conformance criteria and evaluation

The BB Battery, BP Series, sealed, lead acid batteries have been evaluated and verified as conforming with the relevant requirements of the following criteria.

1. SSL Appraisal Specification FAS-101, Version 1.0, 'AS 1603.4-1987, Appendix G, type batteries'.

Limitations/conditions of conformance

Limitations/conditions of conformance, where identified on this certificate, are derived from qualifications from evaluation(s) for conformity and/or other related technical documentation. All details with respect to design, assembly and installation instructions and restrictions should be checked against the producer's current technical manual/data sheets and the requirements of the Authority having Jurisdiction.

Specified limitations/conditions, determined from the evaluation for conformity, include the following.

- i. The manufacturer's instructions, cautions and recommendations, should be observed before the use of the BB Battery, BP Series, sealed, lead acid batteries.

This certification is issued within the scope of CSIRO Verification Services – Rules governing ActivFire Scheme and is valid only for the product(s) as submitted for evaluation and verification of conformity, subject to the following conditions.

- Reference to details, limitations and requirements, where documented as a schedule/enclosure with this certificate.
- The Registrant is responsible for their attestation of conformity and ensuring that on-going production complies with the conformance criteria defined in this certificate.
- This certificate will not be valid if any changes or modifications are made to the product which have not been notified and validated by CSIRO Verification Services.
- This certificate is subject to periodical re-validation upon verification that all requirements, as determined by the conformity assessment body, continue to be satisfactorily met by the Registrant.
- This certificate may only be reproduced in its published form, without modification and inclusive of all schedules/enclosures.
- Any changes, errors or omissions, must be submitted in writing and if necessary or requested, substantiated with relevant evidence.
- Any representations, such as advertising or other marketing related activities or articles shall reflect the correct contents of this certificate and conform with all relevant trade practices and consumer protection legislation and regulations.
- Any terms or conditions of use as applicable to content and documentation as published or accessed through web sites administered by the CSIRO Verification Services.

Issued by

David Whittaker
Executive Officer – ActivFire Scheme



Schedule to Certificate of Conformity

Certificate num.	Registration date	Version	Valid until	
afp - 1228	17-Feb-1999	Number 8	Issue date 1-May-2013	Page 2 of 2

Producer's description

The BB Battery, BP Series, sealed, lead acid batteries are a gas recombination absorbed electrolyte valve regulated sealed batteries. The batteries are completely sealed, leak proof, maintenance free with low self discharge for float or cyclic use applications.

Technical specification

The following details are a representative extract of the technical specification for the BB Battery, BP Series, sealed, lead acid batteries and may be subject to change. Complete and current details should be determined from the designated producer's technical manual/data sheets.

Battery type	Nominal voltage	Rated capacity 20Hr 1.75V/Cell	Casing length	Casing width	Total height	Approximate weight
BP1.2-6	6 V	6 Ah	97 mm	25 mm	56 mm	0.28 kg
BP4-6	6 V	4.0 Ah	70 mm	47 mm	106 mm	0.85 kg
BP4.5-6	6 V	4.5 Ah	70 mm	48 mm	107 mm	0.87 kg
BP5-6	6 V	5.0 Ah	70 mm	48 mm	107mm	0.95 kg
BP6 -6	6 V	6.0 Ah	151 mm	34 mm	94 mm	1.2 kg
BP7 -6	6 V	7.0 Ah	151 mm	34 mm	100 mm	1.2 kg
BP8 -6	6 V	8.0 Ah	151 mm	50 mm	100 mm	1.7 kg
BP10 -6	6 V	10.0 Ah	151 mm	50 mm	100 mm	1.9 kg
BP1.2-12	12 V	1.2 Ah	97 mm	45 mm	59 mm	0.56 kg
BP1.9-12	12 V	1.9 Ah	178 mm	34 mm	65 mm	0.89 kg
BP2.3-12	12 V	2.3 Ah	178 mm	34 mm	65 mm	0.94 kg
BP4 -12	12 V	4.0 Ah	90 mm	70 mm	106 mm	1.7 kg
BP7 -12	12 V	7.0 Ah	151 mm	65 mm	98 mm	2.5 kg
BP12-12	12 V	12.0 Ah	151 mm	98 mm	100 mm	3.95 kg
BP17-12	12 V	17.0 Ah	181 mm	76 mm	167 mm	6.15 kg
BP20-12	12 V	20.0 Ah	181 mm	76 mm	166 mm	6.35 kg
BP24-12	12 V	24.0 Ah	175 mm	166 mm	125 mm	9.1 kg
BP26-12	12 V	26.0 Ah	175 mm	166 mm	125 mm	9.4 kg
BP33-12(S)	12 V	33.0 Ah	195 mm	129 mm	179 mm	11.25 kg
BP40-12	12 V	40.0 Ah	196 mm	165 mm	171 mm	14.0 kg
BP65-12	12 V	65.0 Ah	350 mm	166 mm	174 mm	22.4 kg
BP90-12	12 V	90.0 Ah	329 mm	172 mm	238 mm	33.5 kg
BP120-12	12 V	120.0 Ah	407 mm	173 mm	239 mm	39.5 kg
BP230-12	12 V	230.0 Ah	522 mm	240 mm	240 mm	72.5 kg

The individual performance specifications for the nominated batteries should be sought from the designated supplier.